

CSP-P Seismic Energy Source



The **CSP-P** is a small, light 350 Joule power source intended primarily as a boomer power supply but it can be used with small sparkers.

Recently upgraded, the CSP-P now incorporates dual-voltage technology that allows the operator to tune the sound source to a particular application for improved data quality.

Key Features

- Incorporates dual-voltage technology for exceptional versatility
- Variable Input Power Circuitry for 'soft start'
- Proprietary pulse shaping circuitry for high resolution data
- Additional safety/protection features
- All settings externally selectable
- LED fault indicators
- High current and voltage solid state (semi-conductor) discharge method
- Meets EC emissions regulations enabling interference-free field use
- Supplied in robust transit case, with HV junction box (HVJ2000), mains lead and HV connector plug

Technical Specification

PHYSICAL

Size Transit Case (4U) with cover in place and handles flat: 29cm(H) x 56cm(W) x 56cm(D)
Weight CSP-P, case and cover: 35kg

ELECTRICAL SPECIFICATION

Mains Input 110 or 240Vac (fixed) 45-65Hz@2.0kVA single phase. 3 pin connector
Variable Input Power Circuitry (AVIP) 'soft start' circuitry

Voltage Output 2500 to 3950 Vdc, 4 pin interlocked connector
Solid state semi-conductor discharge method

Output Energy Easy switch selectable in increments
50,100,150,200,300 and 350 Joules

Charging Rate 1500J/second for continuous operation at 0-45°C ambient

CSP-P Technical Specification continued...

| | |
|-----------------|---|
| Capacitance | 48 μ F at 10 ⁸ shot life |
| Trigger | +ve key opto isolated or isolated closure set by front panel switch BNC connector on front panel and remote box (optional) |
| Repetition rate | 6pps max Limited by charge rate, energy level and sound source rating |
| Earth | M8 stainless steel stud on front panel |

SAFETY FEATURES

- Main electronic control circuits and secondary layer of safety circuitry
- Specially designed HV connector with interlock
- High speed dump resistors for high voltage components
- Capacitor bleed resistors
- Open circuit shutdown
- Timer shutdown
- Output current monitor and shutdown
- Over temperature shut-down
- Cover and connector interlocks
- HV fault indicator for internal temperature, low input voltage or capacitor fault
- Remote control available for triggering and operation

The unit's internal design has a modular construction for ease of servicing and capacitor replacement. However, for safety reasons, only Applied Acoustics trained engineers should attempt a repair.

COMPATIBLE SOUND SOURCES

AA201, AA251 and AA301 Boomer plates
Squid 501 Sparker



Due to continual product improvement, specification information may be subject to change without notice.
CSP-P Seismic Energy Source/June 2015
©Applied Acoustic Engineering Ltd.



Applied Acoustic Engineering Ltd

T +44(0)1493 440355
F +44(0)1493 440720
E general@appliedacoustics.com
W www.appliedacoustics.com